# 50-20.200 Cricketfilter® Cloths

## TOP CLOTHS

Amafilter<sup>®</sup> have developed a range of filter cloths specifically designed for our Cricketfilter<sup>®</sup> system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter<sup>®</sup> drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter<sup>®</sup> element top cloth. See our drain cloths datasheets for further details.

#### FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth.
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

#### APPROVALS

Not approved according to 2004/1935/EG or the FDA.

#### RECOMMENDATIONS

Use in combination with drain cloth 50-00.000 to further improve the filtration flux and the lifetime of the top cloth.

### SPECIFICATIONS

| Criteria                                | Detail                  |
|---|-------------------------|
| Cloth code                              | 50-20.200               |
| Cloth use                               | Top cloth               |
| Material                                | PPS                     |
| Cloth structure                         | Multifilament           |
| Surface treatment                       | Heat-set and Calendered |
| Filter fineness (µm)                    | ~1.4                    |
| Air permeability<br>(I/dm²/min) @200 Pa | 3 ± 50%                 |
| Max. Temp. (°C)                         | 150                     |

#### **ORDERING INFORMATION**

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Туре І       | 620    | -             |
|              | 750    | -             |
|              | 1000   | 72415754      |
|              | 1500   | 72415755      |
|              | 2000   | -             |
| Type II      | 1000   | -             |
|              | 1500   | 72487728      |
|              | 2000   | -             |
|              | 2500   | -             |



