10-10.301 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth (Cricketfilter only).

SPECIFICATIONS

| Criteria | Detail |
|--------------------------------------|-------------------------|
| Cloth code | 10-10.301 |
| Cloth use | Top cloth |
| Material | PP |
| Cloth structure | Monofilament |
| Surface treatment | Heat-set and calendered |
| Filter fineness (µm) | ~10 |
| Air permeability (I/dm²/min) @200 Pa | 15 ± 50% |
| Max. Temp. (°C) | 90 |

| Floment Type | Longth | Ordering Code |
|--------------|--------|---------------|
| Element Type | Length | Ordening Code |
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415528 |
| | 1500 | 72415530 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72415531 |
| | 2000 | 72415532 |
| | 2500 | 72415534 |
| PTS 70 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1000 | 72393268 |
| | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| | 2250 | - |
| | 2500 | - |





10-10.306 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

Approved according to FDA, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth.

Wash the filter cloth before use.

SPECIFICATIONS

| Criteria | Detail |
|---|--------------|
| Cloth code | 10-10.306 |
| Cloth use | Top cloth |
| Material | PP |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~45 |
| Air permeability (I/dm²/min) @200 Pa | ~66 |
| Max. Temp. (°C) | 90 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72459725 |
| | 1500 | 72462888 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72432853 |
| | 2000 | - |
| | 2500 | 72432855 |



10-10.309 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|--------------|
| Cloth code | 10-10.309 |
| Cloth use | Top cloth |
| Material | PP |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~60 |
| Air permeability (I/dm²/min) @200 Pa | 90 ± 30% |
| Max. Temp. (°C) | 90 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | - |
| | 1500 | 72415538 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | - |
| | 2000 | 72415539 |
| | 2500 | - |





10-20.200 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|--------------------------------------|-------------------------|
| Cloth code | 10-20.200 |
| Cloth use | Top cloth |
| Material | PP |
| Cloth structure | Multifilament |
| Surface treatment | Heat-set and calendered |
| Filter fineness (µm) | ~8 |
| Air permeability (I/dm²/min) @200 Pa | 15 ± 40% |
| Max. Temp. (°C) | 90 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72462848 |
| | 1500 | - |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72415547 |
| | 2000 | - |
| | 2500 | 72459357 |





10-20.202 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|---------------------------------|
| Cloth code | 10-20.202 |
| Cloth use | Top cloth |
| Material | PP |
| Cloth structure | Multifilament |
| Surface treatment | Singed, heat set and calendered |
| Filter fineness (µm) | ~1 |
| Air permeability (I/dm²/min) @200 Pa | 5 ± 50% |
| Max. Temp. (°C) | 90 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415548 |
| | 1500 | 72415549 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | - |
| | 2000 | - |
| | 2500 | 72415550 |





10-30.200 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

Approved according to FDA, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth.

Wash the filter cloth before use.

SPECIFICATIONS

| Criteria | Detail |
|---|-------------|
| Cloth code | 10-30.200 |
| Cloth use | Top cloth |
| Material | PP |
| Cloth structure | Needle felt |
| Surface treatment | Untreated |
| Filter fineness (µm) | ~20 |
| Air permeability (I/dm²/min) @200 Pa | 420 ± 10% |
| Max. Temp. (°C) | 90 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72381266 |
| | 1500 | 72361434 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72381274 |
| | 2000 | 72373213 |
| | 2500 | - |
| PTS 70 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1000 | - |
| | 1500 | 72421175 |
| | 1750 | - |
| | 2000 | - |
| | 2250 | - |
| | 2500 | 72394903 |





10-40.200 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

Approved according to FDA, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth.

Wash the filter cloth before use.

SPECIFICATIONS

| Criteria | Detail |
|---|---------------|
| Cloth code | 10-40.200 |
| Cloth use | Top cloth |
| Material | PP |
| Cloth structure | Multifilament |
| Surface treatment | Stabilized |
| Filter fineness (µm) | ~30 |
| Air permeability (I/dm²/min) @200 Pa | 75 ± 34% |
| Max. Temp. (°C) | 90 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | - |
| | 1500 | - |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72479582 |
| | 2000 | - |
| | 2500 | 72415559 |





20-10.201 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 20-00.001 to further improve the filtration flux and the lifetime of the top cloth (Cricketfilter only).

SPECIFICATIONS

| Criteria | Detail |
|---|--------------|
| Cloth code | 20-10.201 |
| Cloth use | Top cloth |
| Material | PBT |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~30 |
| Air permeability (I/dm²/min) @200 Pa | 230 ± 20% |
| Max. Temp. (°C) | 150 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72432863 |
| | 1500 | 72432864 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72432865 |
| | 2000 | - |
| | 2500 | 72442397 |
| PTS 70 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1000 | 72381056 |
| | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| | 2250 | - |
| | 2500 | - |





20-10.202 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 20-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|--------------------------------------|--------------|
| Cloth code | 20-10.202 |
| Cloth use | Top cloth |
| Material | PET |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~50 |
| Air permeability (I/dm²/min) @200 Pa | 330 ± 18% |
| Max. Temp. (°C) | 110 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415600 |
| | 1500 | - |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | - |
| | 2000 | 72460071 |
| | 2500 | - |





20-10.300 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 20-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|------------------------------|
| Cloth code | 20-10.300 |
| Cloth use | Top cloth |
| Material | PETP |
| Cloth structure | Monofilament / Multifilament |
| Surface treatment | Heat-set and calendered |
| Filter fineness (µm) | - |
| Air permeability (I/dm²/min) @200 Pa | 15 ± 50% |
| Max. Temp. (°C) | 150 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415608 |
| | 1500 | 72415611 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72415616 |
| | 2000 | 72415617 |
| | 2500 | - |





20-20.102 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth.
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 20-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|---------------|
| Cloth code | 20-20.102 |
| Cloth use | Top cloth |
| Material | PET |
| Cloth structure | Multifilament |
| Surface treatment | Untreated |
| Filter fineness (µm) | - |
| Air permeability (I/dm²/min) @200 Pa | ~20 |
| Max. Temp. (°C) | 90 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| PTS 70 mm | 1500 | 76264450 |
| | 1750 | 70483753 |
| | 2000 | 70491560 |
| PTS 90 mm | 1000 | - |
| | 1500 | 70483747 |
| | 1750 | 70483748 |
| | 2000 | 70480870 |
| | 2250 | 70483751 |
| | 2500 | 70483752 |





32-10.200 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 30-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|--------------|
| Cloth code | 32-10.200 |
| Cloth use | Top cloth |
| Material | PA12 |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~80 |
| Air permeability (I/dm²/min) @200 Pa | 1500 ± 15% |
| Max. Temp. (°C) | 120 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415645 |
| | 1500 | 72415646 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | - |
| | 2000 | 72415648 |
| | 2500 | - |





32-10.301 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 30-00.001 to further improve the filtration flux and the lifetime of the top cloth (Cricketfilter only).

SPECIFICATIONS

| Criteria | Detail |
|---|--------------|
| Cloth code | 32-10.301 |
| Cloth use | Top cloth |
| Material | PA12 |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~40 |
| Air permeability (I/dm²/min) @200 Pa | 300 ± 30% |
| Max. Temp. (°C) | 120 |

| Element Time | Lougarth | Ovelavina Carla |
|--------------|----------|-----------------|
| Element Type | Length | Ordering Code |
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415649 |
| | 1500 | 72415650 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72415652 |
| | 2000 | 72415655 |
| | 2500 | - |
| PTS 70 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1000 | 70483293 |
| | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| | 2250 | - |
| | 2500 | - |





35-10.103 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 30-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|--------------|
| Cloth code | 35-10.103 |
| Cloth use | Top cloth |
| Material | PA 6.6 |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~66 |
| Air permeability (I/dm²/min) @200 Pa | ~156 |
| Max. Temp. (°C) | 110 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | - |
| | 1500 | - |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72432848 |
| | 2000 | - |
| | 2500 | - |





40-40.100 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 40-00.000 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|----------------------------|
| Cloth code | 40-40.100 |
| Cloth use | Top cloth |
| Material | PTFE |
| Cloth structure | Monofilament/Multifilament |
| Surface treatment | Untreated |
| Filter fineness (µm) | ~4 |
| Air permeability (I/dm²/min) @200 Pa | 5 ± 100% |
| Max. Temp. (°C) | 250 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | 72481942 |
| | 750 | - |
| | 1000 | 72415667 |
| | 1500 | 72415674 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72415675 |
| | 2000 | 72433146 |
| | 2500 | 72415677 |





41-10.200 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 41-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|--------------|
| Cloth code | 41-10.200 |
| Cloth use | Top cloth |
| Material | ETFE |
| Cloth structure | Monofilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~25 |
| Air permeability (I/dm²/min) @200 Pa | 275 ± 20% |
| Max. Temp. (°C) | 150 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72432133 |
| | 1500 | 72432134 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72432135 |
| | 2000 | - |
| | 2500 | 72460645 |





45-10.200 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 45-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail | |
|---|--------------|--|
| Cloth code | 45-10.200 | |
| Cloth use | Top cloth | |
| Material | PVDF | |
| Cloth structure | Monofilament | |
| Surface treatment | Calendered | |
| Filter fineness (µm) | ~45 | |
| Air permeability (I/dm²/min) @200 Pa | 210 ± 14% | |
| Max. Temp. (°C) | 110 | |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72432874 |
| | 1500 | 72432878 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | - |
| | 2000 | - |
| | 2500 | - |





45-20.101 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth.
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

SPECIFICATIONS

| Criteria | Detail |
|--------------------------------------|---------------|
| Cloth code | 45-20.101 |
| Cloth use | Top cloth |
| Material | PVDF |
| Cloth structure | Multifilament |
| Surface treatment | Heat set |
| Filter fineness (µm) | - |
| Air permeability (I/dm²/min) @200 Pa | ~7 |
| Max. Temp. (°C) | 110 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| PTS 70 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1000 | - |
| | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| | 2250 | 70483757 |
| | 2500 | - |





45-20.102 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to 2004/1935/EG, declaration of conformity available on request.

RECOMMENDATIONS

Use in combination with drain cloth 45-00.001 to further improve the filtration flux and the lifetime of the top cloth (Cricketfilter only).

SPECIFICATIONS

| Criteria | Detail |
|--------------------------------------|---------------|
| Cloth code | 45-20.102 |
| Cloth use | Top cloth |
| Material | PVDF |
| Cloth structure | Multifilament |
| Surface treatment | Heat set |
| Filter fineness (µm) | - |
| Air permeability (I/dm²/min) @200 Pa | 20 ± 50% |
| Max. Temp. (°C) | 110 |

| E1 1 T | | 0.1.1.0.1 |
|--------------|--------|---------------|
| Element Type | Length | Ordering Code |
| Type I | 620 | - |
| | 750 | - |
| | 1000 | - |
| | 1500 | 72403974 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | - |
| | 2000 | - |
| | 2500 | - |
| PTS 70 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1500 | 70483765 |
| | 1750 | 70483766 |
| | 2000 | - |
| | 2250 | 70483767 |
| | 2500 | _ |



45-40.101 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

SPECIFICATIONS

| Criteria | Detail |
|--------------------------------------|--------------------|
| Cloth code | 45-40.101 |
| Cloth use | Top cloth |
| Material | PVDF |
| Cloth structure | Mono/Multifilament |
| Surface treatment | Heat set |
| Filter fineness (µm) | ~34 |
| Air permeability (I/dm²/min) @200 Pa | ~70 |
| Max. Temp. (°C) | 110 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | - |
| | 1500 | - |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72465665 |
| | 2000 | - |
| | 2500 | - |
| PTS 70 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1500 | 72398380 |
| | 1750 | 70483760 |
| | 2000 | - |
| | 2250 | - |
| | 2500 | - |





50-20.200 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 50-00.000 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|-------------------------|
| Cloth code | 50-20.200 |
| Cloth use | Top cloth |
| Material | PPS |
| Cloth structure | Multifilament |
| Surface treatment | Heat-set and Calendered |
| Filter fineness (µm) | ~1.4 |
| Air permeability (I/dm²/min) @200 Pa | 3 ± 50% |
| Max. Temp. (°C) | 150 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415754 |
| | 1500 | 72415755 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72487728 |
| | 2000 | - |
| | 2500 | - |





50-20.201 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Approved according to FDA, declaration of conformity available on request.

Wash the filter cloth before use.

SPECIFICATIONS

| Criteria | Detail |
|--------------------------------------|---------------|
| Cloth code | 50-20.201 |
| Cloth use | Top cloth |
| Material | PPS |
| Cloth structure | Multifilament |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~5 |
| Air permeability (I/dm²/min) @200 Pa | ~5 |
| Max. Temp. (°C) | 190 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72470030 |
| | 1500 | 72463628 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 72487486 |
| | 2000 | - |
| | 2500 | - |
| PTS 70 mm | 1500 | 72422618 |
| | 1750 | - |
| | 2000 | - |
| PTS 90 mm | 1500 | - |
| | 1750 | - |
| | 2000 | - |
| | 2250 | - |
| | 2500 | - |





50-30.201 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 50-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|-------------|
| Cloth code | 50-30.201 |
| Cloth use | Top cloth |
| Material | PPS |
| Cloth structure | Needle felt |
| Surface treatment | Calendered |
| Filter fineness (µm) | ~15 |
| Air permeability (I/dm²/min) @200 Pa | 100 ± 15% |
| Max. Temp. (°C) | 140 - 160 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | 72415757 |
| | 1500 | 72415758 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | 70479425 |
| | 2000 | - |
| | 2500 | 72460647 |





50-30.202 Cricketfilter® Cloths

TOP CLOTHS

Amafilter® have developed a range of filter cloths specifically designed for our Cricketfilter® system that deliver efficient filtration solutions across a variety of applications. Our range of top cloths are designed to perform with various liquids at varying temperatures and offer the most suitable chemical inertia.

Amafilter® drain cloth are designed to maximize the flux capacity and extends the lifetime of the Cricketfilter® element top cloth. See our drain cloths datasheets for further details.

FEATURES

- High strength seams no breaks. This brings downtime to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It reduces the time required to install a cloth
- Packed in labelled plastic bags to prevent the cloths from contamination.
- Labelled plastic bags to identify the drain cloths.

APPROVALS

Not approved according to 2004/1935/EG or the FDA.

RECOMMENDATIONS

Use in combination with drain cloth 50-00.001 to further improve the filtration flux and the lifetime of the top cloth.

SPECIFICATIONS

| Criteria | Detail |
|---|-----------------------|
| Cloth code | 50-30.202 |
| Cloth use | Top cloth |
| Material | PPS |
| Cloth structure | Needle felt |
| Surface treatment | Calendered / Heat set |
| Filter fineness (µm) | |
| Air permeability (I/dm²/min) @200 Pa | 100 ± 15% |
| Max. Temp. (°C) | 180 |

| Element Type | Length | Ordering Code |
|--------------|--------|---------------|
| Type I | 620 | - |
| | 750 | - |
| | 1000 | - |
| | 1500 | 72474783 |
| | 2000 | - |
| Type II | 1000 | - |
| | 1500 | - |
| | 2000 | - |
| | 2500 | - |

